



Specifications for Keen K-1000 M&T Oven

Part Number	010901 Dual Voltage (120V/240V 1 Phase)
010903 (480V - 3 Phase)	010902 (480V – 1 Phase)
Oven Category	Floor - Mixed Use
Electrode Capacity (LBS) Wire Capacity (# of Spools)	8/10 lb Tubes Filler Metal 18/12" Wire Spools
Electrode Capacity (KGS) Wire Capacity (# of Spools)	8/10 lb Tubes Filler Metal Stored in Door Rack 18/30cm Spools on Shelves
Standard Voltages Available	Dual 120V/240V, , 480V
Wattage	Dual Model is 250W/1000W
Temperature Range (°F)	50-250°F
Temperature Range (°C)	10-121°C
Thermostat	Dial Adjustable
Insulation	2" Thermal Wool
Interior Dimensions (IN)	27.5" x 20.5" x 40"
Interior Dimensions (CM)	68.58cm x 52.07cm x 101.60cm
External Thermometer	Standard
Net Weight (LBS)	296 lbs.
Net Weight (KGS)	134.27 kgs.
Shipping Dimensions (IN)	36" x 42" x 56"
Shipping Dimensions (CM)	91.44cm x 106.68cm x 142.24cm
Shipping Weight (LBS)	331 lbs
Shipping Weight (KGS)	150.14 kgs.
Power Cord Length	8 ft.
Pilot Light	Standard
CSA Approval	No
UL Approval	No
Accessories	None Available
Equal or Similar to:	Phoenix Drywire (24/12" Spools)
Similar Keen Ovens	K-900, K-1000, K-MPO

Keen K-1000 M&T Repair Parts List

Shelf Assembly	Name Plate	Handy Box	Door Pull	Cord (120V)	Replacement Elements
N/A	450103	301038	430102	301014	301026
Cord (240V)	Strain Relief	Strain 240/480V	Pull Catch	Pilot	Thermostat
301018	301041 (120V)	301043	430106	301085	31037